

CORRECTED VERSION

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number  
WO 2005/024148 A1

(51) International Patent Classification<sup>7</sup>: E04B 1/84,  
B04C 3/07

Beach, Wellington, 6010 (NZ). MALONE, James, Mark  
[NZ/NZ]; 29 Bentley Avenue, Glenfield, Auckland, 1310  
(NZ).

(21) International Application Number:  
PCT/NZ2004/000213

(74) Agent: BALDWIN; PO Box 5999, Wellesley Street,  
Auckland, 1001 (NZ).

(22) International Filing Date:  
9 September 2004 (09.09.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
528138 10 September 2003 (10.09.2003) NZ

(71) Applicant (for all designated States except US):  
FLETCHER BUILDING HOLDINGS LIMITED  
[NZ/NZ]; 810 Great South Road, Penrose, Auckland, 1006  
(NZ).


(72) Inventors; and

(75) Inventors/Applicants (for US only): GERLICH, Jo-  
han, Theodoor [NL/NZ]; 22 Teotí Street, Paraparaumu

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: SOUND ATTENUATING FRAMING SYSTEM



(57) Abstract: The resilient plate (2) may be in the form of a nail plate with punched out nails (6) on respective flanges (3) and a resilient connecting portion (5). A plurality of the resilient plates (2) connect spaced apart pairs of studs and top and bottom plates to form a prefabricated building frame such as a wall. The resilient plates (2), utilising mass-spring-mass principles of sound attenuation, will react to sound impacting on the elements of the building frame to provide a required sound attenuation. In alternative embodiments the plate (2) may define a stud and/or may have one of its flanges securable to a masonry or concrete wall.

WO 2005/024148 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(15) Information about Correction:

see PCT Gazette No. 39/2005 of 29 September 2005, Section II

**Published:**

— with international search report

**(48) Date of publication of this corrected version:**

29 September 2005

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*